

GREEN MOISTURE BARRIER

Green Moisture Barrier introduces the next generation of waterproofing with a new, patented self-adhering rubber asphalt compound. Green Moisture Barrier successfully integrates the resilience, flexibility, and superior waterproofing properties of tire rubber into your waterproofing membranes and flashings.



Green Moisture Barrier is ideal for residential and commercial construction.

The product takes waterproofing to a whole new level, while at the same time being the first to comply with new environmental targets of CalGreen and the International Green Building Code.

GWB Roofing

Applications • Chimney Flashing

- Roofing Underlayment
- Window Flashing
- Through Wall Flashing
- Deck Systems
- Waterproofing Block and Poured Concrete Foundations

- **Features** Contains 15% plus Recycled Tire Rubber
 - Suitable for coatings from 10 mil to 80 mil
 - Compatible with all surface films

- **Benefits** Superior heat resistance (up to 300°F)
 - Excellent low temp flexibility (-30°F)
 - Passes ASTM D1907
 - Excellent adhesion even todifficult surfaces
 - Qualifies for LEED point contribution
 - Technical service and design support

GWB Applications



greenmoisturebarrier.com

Deccofelt Corporation PO Box 156 555 S. Vermont Avenue Glendora, CA 91740

t 800.725.1414

626.963.8511

626.914.2734

• info@deccofelt.com

626.963.8511

